


UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPLICATE

Form approved.
Budget Bureau No. 1004-0136
Expires December 31, 1991



APPLICATION FOR PERMIT TO DRILL OR DEEPEN

1a. TYPE OF WORK DRILL <input checked="" type="checkbox"/> DEEPEN <input type="checkbox"/>		7. UNIT AGREEMENT NAME RED WASH	
b. TYPE OF WELL OIL WELL <input type="checkbox"/> GAS-WELL <input checked="" type="checkbox"/> OTHER <input type="checkbox"/> SINGLE ZONE <input type="checkbox"/> MULTIPLE ZONE <input type="checkbox"/>		8. FARM OR LEASE NAME, WELL NO. #311	
2. NAME OF OPERATOR CHEVRON USA PRODUCTION CO., INC.		9. API WELL NO.	
3. ADDRESS AND TELEPHONE NO. 11002 EAST, 17500 SOUTH, VERNAL, UT 84078-8526 (801) 781-4300		10. FIELD AND POOL, OR WILDCAT RED WASH GREEN RIVER	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements)* At surface 1512' FSL, 1370' FWL, NESW At proposed prod. zone SAME		11. SEC., T., R., M., OR BLOCK AND SURVEY OR AREA SEC. 26-T7S-R24E, SLB&M	
14. DISTANCE IN MILES AND DIRECTION FROM NEAREST TOWN OR POST OFFICE* 31.4 MILES FROM VERNAL, UT		12. COUNTY OR PARISH UINTAH	13. STATE UTAH
15. DISTANCE FROM PROPOSED* LOCATION TO NEAREST PROPERTY OR LEASE LINE, FT. (Also to nearest drlg. unit line, if any) 1129'	16. NO. OF ACRES IN LEASE 2560	17. NO. OF ACRES ASSIGNED TO THIS WELL NA	
18. DISTANCE FROM PROPOSED LOCATION* TO NEAREST WELL, DRILLING, COMPLETED, OR APPLIED FOR, ON THIS LEASE, FT. 2627'	19. PROPOSED DEPTH 5218'	20. ROTARY OR CABLE TOOLS ROTARY	
21. ELEVATIONS (Show whether DF, RT, GR, etc.) 5662' GL		22. APPROX. DATE WORK WILL START* 2/1/95	

PROPOSED CASING AND CEMENTING PROGRAM

SIZE OF HOLE	GRADE, SIZE OF CASING	WEIGHT PER FOOT	SETTING DEPTH	QUANTITY OF CEMENT
12-1/4"	8-5/8" K-55	24#	360'	190 SX.
7-7/8"	5-1/2" K-55	15.5#	5218'	602 SX.

We propose to drill for natural gas in the Green River Formation at the location specified. Enclosures:

- Certified Plat
- Self-Certification Statement
- Thirteen Point Surface Use Plan With Attachments
- Eight Point Drilling Plan With Attachments

IN ABOVE SPACE DESCRIBE PROPOSED PROGRAM: If proposal is to deepen, give data on present productive zone and proposed new productive zone. If proposal is to drill or deepen directionally, give pertinent data on subsurface locations and measured and true vertical depths. Give blowout preventer program, if any.

24. SIGNED [Signature] TITLE TEAM LEADER DATE 12-19-94

(This space for Federal or State office use)

PERMIT NO. 43-047-32628

APPROVAL DATE

APPROVED BY THE STATE

Application approval does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

CONDITIONS OF APPROVAL, IF ANY:

APPROVED BY

TITLE

*See Instructions On Reverse Side

DATE: 1/23/95
BY: [Signature]
WELL SPACING: R649-2-3



T7S, R24E, S.L.B.&M.

CHEVRON U.S.A., INC.

Well location, RED WASH UNIT #311, located as shown in the NE 1/4 SW 1/4 of Section 26, T7S, R24E, S.L.B.&M. Uintah County, Utah.

BASIS OF ELEVATION

SPOT ELEVATION AT THE NORTHEAST CORNER OF SECTION 26, T7S, R24E, S.L.B.&M. TAKEN FROM THE DINOSAUR NW, QUADRANGLE, UTAH, UINTAH COUNTY, 7.5 MINUTE QUAD. (TOPOGRAPHIC MAP) PUBLISHED BY THE UNITED STATES DEPARTMENT OF THE INTERIOR, GEOLOGICAL SURVEY. SAID ELEVATION IS MARKED AS BEING 5716 FEET.



CERTIFICATE

THIS IS TO CERTIFY THAT THE ABOVE PLAT WAS PREPARED FROM FIELD NOTES OF ACTUAL SURVEYS MADE BY ME OR UNDER MY SUPERVISION AND THAT THE SAME ARE TRUE AND CORRECT TO THE BEST OF MY KNOWLEDGE AND BELIEF.

Robert L. Kay
 REGISTERED LAND SURVEYOR
 REGISTRATION NO. 181319
 STATE OF UTAH

LEGEND:

- └ = 90° SYMBOL
- = PROPOSED WELL HEAD.
- ▲ = SECTION CORNERS LOCATED. (Brass Caps)

UINTAH ENGINEERING & LAND SURVEYING

85 SOUTH 200 EAST - VERNAL, UTAH 84078

(801) 789-1017

SCALE 1" = 1000'	DATE SURVEYED: 9-22-94	DATE DRAWN: 10-29-94
PARTY B.B. D.G. D.J.S.	REFERENCES G.L.O. PLAT	
WEATHER WARM	FILE CHEVRON U.S.A., INC.	

CHEVRON USA PRODUCTION CO.

**RED WASH UNIT #311
1512' FSL & 1370' FWL
NESW-S26-T7S-R24E, SLB&M
UINTAH COUNTY, UTAH**

EIGHT POINT DRILLING PLAN

1. ESTIMATED FORMATION TOPS:

Uinta	Surface
Green River	~2360' to 5218' TD

**2. ESTIMATED DEPTHS OF TOP AND BOTTOM OF WATER, OIL, GAS, OR
OTHER MINERAL BEARING FORMATIONS AND PLAN FOR PROTECTION:**

Deepest Fresh Water: ~2360', top of Green River Formation. The Green River Formation is classified as an exempt aquifer in the vicinity of the proposed well.

Oil Shale: Oil shale is expected between the depths of ~3421-3524'.

Oil: None expected.

Gas: Possible gas in the Uinta Fm. below ~2100'. Expected in the Green River Fm. from ~3768' to 5068'.

Protection of oil, gas, water, or other mineral bearing formations:
Protection shall be accomplished by cementing surface casing and production casing back to the surface or to depths sufficient to isolate required formations. Please refer to casing and cement information for protection plans.

3. PRESSURE CONTROL EQUIPMENT:

For drilling surface hole to 360': No BOP equipment required.

For drilling through 8.625" surface casing to TD:

Maximum anticipated surface pressure is <1400 psi.

Pressure control equipment shall be in accordance with BLM minimum standards for 2000 psi equipment.

RED WASH UNIT #311 - EIGHT-POINT DRILLING PLAN

A casing head with an 11", 3000 psi flange will be screwed or welded onto the 8.625" surface casing.

BOP stack will consist of a double gate and annular preventer. The double gate will be equipped with pipe rams on bottom and blind rams on top. The choke and kill lines will be connected to outlets between the bottom and top rams, utilizing either the ram body outlet or a drilling spool with side outlets. The BOP stack will be 9" or 11" bore, 2000 or 3000 psi working pressure. The choke and kill lines will be 2" or 3" bore, 2000 or 3000 psi working pressure. Please refer to attached schematics.

A rotating head may be used while drilling below surface casing for control of gas cut mud.

Test procedure and frequency shall be in accordance with BLM minimum standards for 2000 psi equipment.

4. SUPPLEMENTAL DRILLING EQUIPMENT AND CASING INFORMATION:

Casing Information:

Casing	Conn.	New/ Used	Stage Tool	Centralizers
8.625"	STC	New	No	10' above shoe, on 1st and 3rd collars.
5.500"	STC	New	No	10' above shoe, every other collar to top of pay ($\pm 3750'$),

Cement Information:

Casing	Cement
8.625"	Oilfield type cement circulated in. Class "A" single slurry mixed to 15.6 ppg, yield = 1.19 cf/sx. Fill to surface with 225 cf (190 sx) calculated. Tail plug used. Allowed to set under pressure.
5.500"	Lead/Tail oilfield type cement circulated in. Tail slurry: 50/50 Class H/Pozzolan + 2% gel + additives as required mixed to 14.1 ppg, yield = 1.23 cf/sx; or class G + 12.5 lb/sx gilsonite + additives as required mixed to 14.8 ppg, yield =

RED WASH UNIT #311 - EIGHT-POINT DRILLING PLAN

1.34. Fill to 3450' ($\pm 300'$ above top of pay) with 405 cf (329 sx or 302 sx).

Lead slurry: Class "A" + extender + additives mixed to 11.0 ppg, yield = 3.82 cf/sx. Fill to surface with 1041 cf (273 sx).

Tail plug used. Allowed to set under pressure.

Drilling Equipment:

Surface hole will be drilled and surface casing set with small rotary surface hole rig.

A rotating head may be used while drilling below surface casing for control of gas cut mud.

5. CIRCULATING MEDIUM, MUD TYPE, MINIMUM QUANTITIES OF WEIGHT MATERIAL, AND MONITORING EQUIPMENT:

Surface hole will be drilled with air, air/mist, foam, or mud depending on hole conditions. Drilling below surface casing will be with water based drilling fluids consisting primarily of fresh water, bentonite, lignite, caustic, lime, soda ash, and polymers. No chromates will be used. It is not intended to use oil in the mud, however, in the event it is used, oil concentration will be less than 4% by volume. Maximum anticipated mud weight is ± 9.5 ppg.

No minimum quantity of weight material will be required to be kept on location.

PVT/Flow Show will be used from base of surface casing to TD.

Gas detector will be used from 3500' (depth mud loggers on) to TD.

6. ANTICIPATED TYPE AND AMOUNT OF TESTING, LOGGING, AND CORING:

Logging:

Mud logging:	~3500' to TD.
Dual Induction/SP/GR:	TD-Surface casing shoe
Density/Neutron/GR with XY caliper:	TD-3500'
Sonic/GR with caliper	TD-Surface casing shoe.
MIR tool:	TD-3500'

RED WASH UNIT #311 - EIGHT-POINT DRILLING PLAN

Coring:

None planned.

Testing:

Possible DST in lower Green River Fm. at wellsite geologist's discretion.

7. EXPECTED BOTTOM HOLE PRESSURE AND ANY ANTICIPATED ABNORMAL PRESSURE, TEMPERATURES, OR OTHER HAZARDS (H₂S, STEAM, ETC.) AND ASSOCIATED CONTINGENCY PLANS:

Normal pressure gradient to top of Green River Fm. Some slightly pressured (0.47 psi/ft.) gas zones within the Green River Fm. may exist, although possible pressure depleted intervals (0.37 psi/ft.) from 3768' to 5068' are viewed as greater hazards. All sands typically tight - drill underbalanced with water or unweighted mud.

Maximum expected BHP @ 5215': ~2450 psi (0.47 psi/ft.).

Maximum expected BHT @ 5215': ~135° F.

No other abnormal hazards are anticipated and no contingency plans are required.


8. OTHER:

None.

E. CLASS III BLOWOUT PREVENTER STACK:

The Class III preventer stack is designed for drilling or workover operations. It is composed of a single hydraulically operated annular preventer on top, then a blind ram preventer, a drilling spool, and a single pipe ram preventer on bottom. The choke and kill lines are installed onto the drilling spool and must have a minimum internal diameter of 2". All side outlets on the preventers or drilling spool must be flanged, studded, or clamped. An emergency kill line may be installed on the wellhead. A double ram preventer should only be used when space limitations make it necessary to remove the drilling spool. In these instances, the choke manifold should be connected to a flanged outlet between the preventer rams only. In this hookup, the pipe rams are considered master rams only, and cannot be used to routinely circulate out a kick. The Class III blowout preventer stack is shown to the right in Figure 11J.4.

Figure 11J.4
Class III Blowout Preventer Stack




CHEVRON DRILLING REFERENCE SERIES
VOLUME ELEVEN
WELL CONTROL AND BLOWOUT PREVENTION

D. CLASS III CHOKE MANIFOLD

The Class III choke manifold is suitable for Class III workovers and drilling operations. The Standard Class III choke manifold is shown in Figure 11J.8 below. Specific design features of the Class III manifold include:

1. The manifold is attached to a drilling spool or the top ram preventer side outlet.
2. The minimum internal diameter is 2" (nominal) for outlets, flanges, valves and lines.
3. Includes two steel gate valves in the choke line at the drilling spool outlet. The inside choke line valve may be remotely controlled (HCR).
4. Includes two manually adjustable chokes which are installed on both side of the manifold cross. Steel isolation gate valves are installed between both chokes and the cross, and also downstream of both chokes.
5. Includes a bleed line which runs straight through the cross and is isolated by a steel gate valve.
6. Includes a valve isolated pressure gauge suitable for drilling service which can display the casing pressure within view of the choke operator.
7. Returns through the choke manifold must be divertible through a mud-gas separator and then be routed to either the shale shaker or the reserve pit through a buffer tank or manifold arrangement.
8. If the choke manifold is remote from the wellhead, a third master valve should be installed immediately upstream of the manifold cross.




CHEVRON DRILLING REFERENCE SERIES
VOLUME ELEVEN
WELL CONTROL AND BLOWOUT PREVENTION

D. TYPE "B" KILL LINE — CLASS III, IV , AND V WELLS

The type B kill line described below in Figure 11J.11 is the minimum recommended hookup for installation on all Class III, Class IV and Class V wells. Specific design features of the type B kill line include:

1. The preferred kill line connection to the well is at the drilling spool, however, a preventer side outlet may be used when space restrictions exclude the use of a drilling spool. In all cases, the kill line must be installed below the uppermost blind rams so the well can be pumped into with no pipe in the hole.
2. The arrangement includes two - 2" (nominal) gate valves installed at the drilling spool and an upstream fluid cross. The outside valve may be hydraulically remote controlled.
3. Two pump-in lines should be attached to the fluid cross. The **primary kill line** should be routed to the rig standpipe where it can be manifolded to the rig pumps. The **remote kill line** should be run to a safe location away from the rig or to the rig cementing unit. The remote kill line should have a loose end connection for rigging-up a high pressure pumping unit.
4. Both the primary kill line and the remote kill line must include a 2" check valve which is in working condition while drilling. If a check valve is crippled for testing purposes, the flapper or ball must be re-installed and tested before drilling resumes.
5. The primary kill line must include a pressure gauge which can display the pump-in pressure on the rig floor.
6. Any lines which are installed at the wellhead are designated as "**emergency kill lines**" and should only be used if the primary and remote kill lines are inoperable.



United States Department of the Interior
Bureau of Land Management
Vernal District Office
170 South 500 West
Vernal, UT 84078

SELF-CERTIFICATION STATEMENT

Be advised that Chevron USA Production Company is considered to be the operator of Red Wash Unit #311, NESW-Sec.26-T7S-R24E, Uintah County, Utah, and is responsible under the terms and conditions of the lease for the operations conducted on the leased lands.

Bond coverage for this well is provided by Nationwide Bond #U-89-75-81-34 (Standard Oil Co. of California and its wholly owned subsidiary Chevron USA Production Co., as co-principals) via surety consent as provided for in 43 CFR 3104.2.

Sincerely,



J. T. Conley
Red Wash Area Team Leader

DATE: 12-19-94

CHEVRON USA PRODUCTION CO.

**RED WASH UNIT #311
1512' FSL & 1370' FWL
NESW-S26-T7S-R24E, SLB&M
UINTAH COUNTY, UTAH**

THIRTEEN POINT SURFACE USE PLAN

1. EXISTING ROADS:

A. See Topographic Map A. There are no plans to change, alter or improve upon any existing state or county road.

B. See Topographic Map A. Travel east from Vernal on U.S. Highway 40 to the intersection with Utah State Highway 45. Turn south on Utah State 45 and proceed 20.7 miles to the Red Wash Oil and Gas Field road. Turn east and proceed 4.7 miles to existing lease road past water tank. Turn south and proceed a total of 5.6 miles on existing lease road to proposed access road.

2. ACCESS ROADS TO BE CONSTRUCTED OR RECONSTRUCTED:

See Topographic Maps A and B. The access road and location site are on Federal lands. A new access road of approximately 0.4 miles to the location will be constructed.

3. LOCATION OF EXISTING WELLS WITHIN ONE MILE:

See Topographic Map B.

4. LOCATION OF EXISTING OR PROPOSED FACILITIES IF WELL IS PRODUCTIVE:

A. See Topographic Map C.

B. Gas dehydration and metering equipment will be installed onsite following completion of the new wellbore. No blooie pit will be constructed, as a tank will be installed in its place.

RWU #311 - THIRTEEN POINT SURFACE USE PLAN

C. A gas pipeline approximately 2300' in length will be constructed to connect the well to the existing gas gathering system. The pipeline will follow the proposed access road to the tie-in.

D. Disturbed areas no longer needed for operations will be graded back to as near original state as possible. Drainage channels will be returned to original state and the areas will be reseeded as prescribed by the BLM.

5. LOCATION AND TYPE OF WATER SUPPLY:

Red Wash Unit fresh water supply, Application #A17791, Water Right Number 49-2153. Water will be picked up at water tank shown on Topographic Map A, ~6 miles from wellsite on proposed access route.

Transportation of water shall be by tank truck.

6. CONSTRUCTION MATERIALS:

Native dirt and gravel will be used as construction materials.

7. METHODS FOR HANDLING WASTE DISPOSAL:

A. A closed mud system is planned, requiring a trench for the reserve tank.

B. Excess reserve pit fluid will be disposed of via haul-off to a commercial disposal facility.

C. Drill cuttings will be caught and settled in the reserve tank and buried when the trench is backfilled.

D. Commercial service will provide portable toilets and haul-off to a commercial disposal facility.

E. Trash will be stored in trash containers and hauled to commercial or municipal facility for disposal.

F. It is not anticipated that any salt or chemicals will need to be disposed of. If required, disposal will be by commercial disposal facility.

RWU #311 - THIRTEEN POINT SURFACE USE PLAN

G. In the event fluids are produced, any gas and associated condensate will be flared over the flare pit while testing. Any produced water will be caught in the flare pit and transferred to Red Wash Central Battery for use in the waterflood system. Depending on the nature of completion/stimulation fluids, these will be caught in the flare pit and disposed of via use in the waterflood system, evaporation or haul-off to a commercial disposal facility.

H. Hazardous chemicals 10,000lb. of which will most likely be used, produced, stored, transported or disposed of in association with the proposed action of drilling, completing and producing this well: We anticipate that none of the hazardous chemicals in quantities of 10,000 lb. or more will be associated with these operations.

I. Extremely hazardous substances threshold quantities of which will be used, produced, stored, transported or disposed of in association with the proposed action of drilling, completing and producing this well: We anticipate that none of the extremely hazardous substances in threshold quantities per 40 CFR 355 will be associated with these operations.

8. ANCILLARY FACILITIES:

None.

9. WELLSITE LAYOUT:

A. See Figures 1 and 2. A closed mud system is planned. In the event that a closed mud system is not available, a reserve pit will be constructed as shown. The reserve pit will be lined if required.

B. Burn pit will not be lined.

C. Access to the well pad will be as shown on Topographic Map B.

10. PLAN FOR RESTORATION OF SURFACE:

A. All surface areas not required for production operations will be graded to as near original condition as possible and contoured to maintain possible erosion to a minimum. Any rock encountered in excavation will be disposed of beneath backfill to return surface to its present appearance and provide soil for seed growth.

RWU #311 - THIRTEEN POINT SURFACE USE PLAN

B. The topsoil will be evenly distributed over the disturbed areas. Reseeding will be performed as directed by the BLM.

C. Pits that would present a hazard to wildlife or livestock will be backfilled when the rig is released and removed.

D. Completion of the well is planned during 1995. Rehabilitation will commence following completion of the well. If the wellsite is to be abandoned, all disturbed areas will be recontoured to the natural contour as soon as possible.

11. SURFACE OWNERSHIP:

The wellsite, access roads and flowlines are on Federal land. The operator shall contact the BLM office at (801) 789-1362 between 24 and 48 hours prior to construction activities.

12. OTHER INFORMATION:

A. The well is located in hilly and sandy terrain. Vegetation consists of sagebrush and natural grasses around the location. The soil is a poorly developed, semi-arid, thin topsoil layer over the Uintah Formation.

B. Surface use activities other than the oil and gas well facilities consist of grazing.

C. There are no occupied dwellings near the wellsite.

D. Archeological clearance was recommended during a 12/16/94 meeting between BLM, Chevron and Senco-Phenix personnel.


RWU #311 - THIRTEEN POINT SURFACE USE PLAN

13. COMPANY REPRESENTATIVE:

Mr. J. T. Conley
11002 East 17500 South
Vernal, UT 84078
(801) 781-4301

I hereby certify that I, or persons under my direct supervision, have inspected the proposed drillsite and access route; that I am familiar with the conditions which presently exist; that the statements made in this plan are, to the best of my knowledge, true and correct; and, that the work associated with the operations proposed herein will be performed by Chevron USA Production Co., Inc. and its contractors and subcontractors in conformity with this plan and the terms and conditions under which it is approved.

12-19-94
Date




J. T. Conley
Red Wash Area Team Leader

CHEVRON USA, INC.


LOCATION LAYOUT FOR

RED WASH UNIT #311
SECTION 26, T7S, R24E, S.L.B.&M.
1512' FSL 1370' FWL



SCALE: 1" = 50'
DATE: 10-29-94
Drawn By: D.J.S.

R. Kay



Elev. Ungraded Ground at Location Stake = 5662.2'
Elev. Graded Ground at Location Stake = 5661.7'

FIGURE #1
UINTAH ENGINEERING & LAND SURVEYING
85 So. 200 East • Vernal, Utah 84078 • (801) 789-1017


CHEVRON USA., INC.

TYPICAL CROSS SECTIONS FOR

RED WASH UNIT #311

SECTION 26, T7S, R24E, S.L.B.&M.

1512' FSL 1370' FWL



DATE: 10-29-94
Drawn By: D.J.S.

Handwritten signature and stamp





FIGURE #2

CUT APPROXIMATE YARDAGES

(6") Topsoil Stripping	= 1,320 Cu. Yds.
Remaining Location	= 5,050 Cu. Yds.
TOTAL CUT	= 6,370 CU.YDS.
FILL	= 2,590 CU.YDS.

EXCESS MATERIAL AFTER 5% COMPACTION	= 3,640 Cu. Yds.
Topsoil & Pit Backfill (1/2 Pit Vol.)	= 2,920 Cu. Yds.
EXCESS CUT MATERIAL	= 720 Cu. Yds.

UINTAH ENGINEERING & LAND SURVEYING
85 So. 200 East • Vernal, Utah 84078 • (801) 789-1017




TOPOGRAPHIC
MAP "A"

DATE: 10-28-94 J.D.S.



CHEVRON U.S.A. INC.

RED WASH UNIT #311
SECTION 26, T7S, R24E, S.L.B.&M.
1512' FSL 1370' FWL




**TOPOGRAPHIC
MAP "B"**

SCALE: 1" = 2000'
DATE: 10-28-94 J.D.S.



CHEVRON U.S.A. INC.

RED WASH UNIT #311
SECTION 26, T7S, R24E, S.L.B.&M.
1512' FSL 1370' FWL



TOPOGRAPHIC
MAP "C"

LEGEND:

- EXISTING PIPELINE
 - - - - - Proposed Pipeline



CHEVRON U.S.A. INC.

RED WASH UNIT #311
 SECTION 26, T7S, R24E, S.L.B.&M.

DATE: 10-28-94 J.D.S.

WORKSHEET
APPLICATION FOR PERMIT TO DRILL

APD RECEIVED: 12/21/94

API NO. ASSIGNED: 43-047-32628

WELL NAME: RED WASH #311
OPERATOR: CHEVRON USA PRODUCTION (N0210)

PROPOSED LOCATION:

NESW 26 - T07S - R24E
SURFACE: 1512-FSL-1370-FWL
BOTTOM: 1512-FSL-1370-FWL
UINTAH COUNTY
RED WASH FIELD (665)

LEASE TYPE: FED
LEASE NUMBER: SL-071965

PROPOSED PRODUCING FORMATION: GRRV

INSPECT LOCATION BY: / /

TECH REVIEW	Initials	Date
Engineering		
Geology		
Surface		

RECEIVED AND/OR REVIEWED:

Y Plat
Y Bond: Federal ☒ State ☐ Fee ☐
(Number 4-89-75-81-34)
N Potash (Y/N)
N Oil shale (Y/N)
Y Water permit
(Number 49-2153)
N RDCC Review (Y/N)
(Date: _____)

LOCATION AND SITING:

☒ R649-2-3. Unit: UTU630/0X
____ R649-3-2. General.
____ R649-3-3. Exception.
____ Drilling Unit.
Board Cause no: _____
Date: _____

COMMENTS: _____

STIPULATIONS: _____



State of Utah
DEPARTMENT OF NATURAL RESOURCES
DIVISION OF OIL, GAS AND MINING

Michael O. Leavitt
Governor

Ted Stewart
Executive Director

James W. Carter
Division Director

355 West North Temple
3 Triad Center, Suite 350
Salt Lake City, Utah 84180-1203
801-538-5340
801-359-3940 (Fax)
801-538-5319 (TDD)

January 23, 1995

Chevron USA Production Company, Inc.
11002 East 17500 South
Vernal, Utah 84078

Re: Red Wash #311 Well, 1512' FSL, 1370' FWL, NE SW, Sec. 26, T. 7 S., R. 24 E.,
Uintah County, Utah

Gentlemen:

Pursuant to Utah Code Ann. § 40-6-18, (1953, as amended), Utah Admin. R. 649-2-3, Application of Rules to Unit Agreements and R. 649-3-4, Permitting of Wells to be Drilled, Deepened or Plugged-Back, approval to drill the referenced well is hereby granted.

In addition, the following specific actions are necessary to fully comply with this approval:

1. Compliance with the requirements of Utah Admin. R. 649-1 et seq., the Oil and Gas Conservation General Rules.
2. Notification to the Division within 24 hours after drilling operations commence.
3. Submittal of Entity Action Form, Form 6, within five working days following commencement of drilling operations and whenever a change in operations or interests necessitates an entity status change.
4. Submittal of the Report of Water Encountered During Drilling, Form 7.
5. Prompt notification prior to commencing operations, if necessary, to plug and abandon the well. Notify Frank R. Matthews, Petroleum Engineer, (Office) (801)538-5340, (Home) (801)476-8613, or K. Michael Hebertson, Reclamation Specialist, (Home) (801)269-9212.



Page 2

Chevron USA Production Company, Inc.


Red Wash #311 Well

January 23, 1995

6. Compliance with the requirements of Utah Admin. R. 649-3-20, Gas Flaring or Venting, if the well is completed for production.

This approval shall expire one year after date of issuance unless substantial and continuous operation is underway or a request for an extension is made prior to the approval expiration date. The API number assigned to this well is 43-047-32628.

Sincerely,



R.J. Firth
Associate Director

ldc

Enclosures

cc: Uintah County Assessor

Bureau of Land Management, Vernal District Office

WOI1

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPLICATE*
(Other instructions on
reverse side)

Form approved.
Budget Bureau No. 1004-0136
Expires December 31, 1991

APPLICATION FOR PERMIT TO DRILL OR DEEPEN

1a. TYPE OF WORK

DRILL ☒ DEEPEN ☐

b. TYPE OF WELL

OIL WELL ☐ GAS-WELL ☒ OTHER ☐ SINGLE ZONE ☐ MULTIPLE ZONE ☐

2. NAME OF OPERATOR
CHEVRON USA PRODUCTION CO., INC.

3. ADDRESS AND TELEPHONE NO.
11002 EAST, 17500 SOUTH, VERNAL, UT 84078-8526 (801) 781-4300

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements)*

At surface

1512' FSL, 1370' FWL, NESW

At proposed prod. zone

SAME

14. DISTANCE IN MILES AND DIRECTION FROM NEAREST TOWN OR POST OFFICE*
31.4 MILES FROM VERNAL, UT

15. DISTANCE FROM PROPOSED*
LOCATION TO NEAREST
PROPERTY OR LEASE LINE, FT.
(Also to nearest drilg. unit line, if any) 1129'

16. NO. OF ACRES IN LEASE

2560

17. NO. OF ACRES ASSIGNED
TO THIS WELL

NA

18. DISTANCE FROM PROPOSED LOCATION*
TO NEAREST WELL, DRILLING, COMPLETED,
OR APPLIED FOR, ON THIS LEASE, FT. 2627'

19. PROPOSED DEPTH

5218'

20. ROTARY OR CABLE TOOLS

ROTARY

21. ELEVATIONS (Show whether DF, RT, GR, etc.)
5662' GL

22. APPROX. DATE WORK WILL START*
2/1/95

PROPOSED CASING AND CEMENTING PROGRAM

SIZE OF HOLE	GRADE, SIZE OF CASING	WEIGHT PER FOOT	SETTING DEPTH	QUANTITY OF CEMENT
12-1/4"	8-5/8" K-55	24#	360'	190 SX.
7-7/8"	5-1/2" K-55	15.5#	5218'	602 SX.

We propose to drill for natural gas in the Green River Formation at the location specified. Enclosures:

- Certified Plat
- Self-Certification Statement
- Thirteen Point Surface Use Plan With Attachments
- Eight Point Drilling Plan With Attachments

JAN 1 1995

OFFICE OF OIL, GAS & MINERALS

RECEIVED
DEC 22 1994

IN ABOVE SPACE DESCRIBE PROPOSED PROGRAM: If proposal is to deepen, give data on present productive zone and proposed new productive zone. If proposal is to drill or deepen directionally, give pertinent data on subsurface locations and measured and true vertical depths. Give blowout preventer program, if any.

24. SIGNED [Signature] TITLE TEAM LEADER DATE 12-19-94

(This space for Federal or State office use)

PERMIT NO.

NOTICE OF APPROVAL

APPROVAL DATE

CONDITIONS OF APPROVAL ATTACHED
TO OPERATOR'S COPY

Application approval does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.
CONDITIONS OF APPROVAL, IF ANY:

APPROVED BY

TITLE

ASSISTANT DISTRICT
MANAGER MINERALS

DATE

JAN 24 1995

*See Instructions On Reverse Side

CONDITIONS OF APPROVAL
APPLICATION FOR PERMIT TO DRILL

Company/Operator: Chevron USA Production Co., Inc.

Well Name & Number: Red Wash 311

API Number: 43-047-32628

Lease Number: SL-071965

Location: NESW Sec. 26 T. 7S R. 24E

NOTIFICATION REQUIREMENTS

- | | | |
|---------------------------------|---|---|
| Location Construction | - | at least forty-eight (48) hours prior to construction of location and access roads. |
| Location Completion | - | prior to moving on the drilling rig. |
| Spud Notice | - | at least twenty-four (24) hours prior to spudding the well. |
| Casing String and Cementing | - | at least twenty-four (24) hours prior to running casing and cementing all casing strings. |
| BOP and Related Equipment Tests | - | at least twenty-four (24) hours prior to initiating pressure tests. |
| First Production Notice | - | within five (5) business days after new well begins, or production resumes after well has been off production for more than ninety (90) days. |

For more specific details on notification requirements, please check the Conditions of Approval for Notice to Drill and Surface Use Program.

CONDITIONS OF APPROVAL FOR NOTICE TO DRILL

Approval of this application does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

All lease and/or unit operations will be conducted in such a manner that full compliance is made with applicable laws, regulations (43 CFR 3100), Onshore Oil and Gas Orders, and the approved plan of operations. The operator is fully responsible for the actions of his subcontractors. A copy of these conditions will be furnished to the field representative to insure compliance.

Be aware fire restrictions may be in effect when location is being constructed and/or when well is being drilled. Contact the appropriate Surface Management Agency for information.

A. DRILLING PROGRAM

1. Estimated Depth at Which Oil, Gas, Water, or Other Mineral Bearing Zones are Expected to be Encountered

Report ALL water shows and water-bearing sands to Tim Ingwell of this office. Copies of State of Utah form OGC-8-X are acceptable. If noticeable water flows are detected, submit samples to this office along with any water analyses conducted.

All usable water and prospectively valuable minerals (as described by BLM at onsite) encountered during drilling, will be recorded by depth and adequately protected. All oil and gas shows will be tested to determine commercial potential.

2. Pressure Control Equipment

The surface BOP and related equipment shall meet the minimum requirements of Onshore Oil and Gas Order No. 2 for a 2M system for equipment and testing requirements, procedures, etc., and individual components shall be operable as designed. A test plug will need to be used in testing the BOPE. Chart recorders shall be used for all pressure tests.

Test charts, with individual test results identified, shall be maintained on location while drilling and shall be made available to a BLM representative upon request.

The Vernal District Office shall be notified, at least 24 hours prior to initiating the pressure tests, in order to have a BLM representative on location during pressure testing.

3. Casing Program and Auxiliary Equipment

Surface casing shall have centralizers on the bottom three joints, with a minimum of one centralizer per joint.

As a minimum, the usable water and oil shale resources shall be isolated and/or protected by having a cement top for the production casing at least 200' above the Uinta/Green River contact identified at $\pm 3065'$. If gilsonite is encountered while drilling, it shall be isolated and/or protected via the cementing program.

The Vernal District Office shall be notified at least 24 hours prior to the running and cementing of all casing strings, in order to have a BLM representative on location while running and cementing all casing strings.

4. Mud Program and Circulating Medium

As per Onshore Oil and Gas Order No. 2 sufficient quantities of mud materials will be maintained or readily accessible for the purpose of well control.

Hazardous substances specifically listed by the EPA as a hazardous waste or demonstrating a characteristic of a hazardous waste will not be used in drilling, testing, or completion operations.

No chromate additives will be used in the mud system on Federal and Indian lands without prior BLM approval to ensure adequate protection of fresh water aquifers.

5. Coring, Logging and Testing Program

Daily drilling and completion progress reports shall be submitted to this office on a weekly basis.

All Drill Stem tests (DST) shall be accomplished during daylight hours, unless specific approval to start during other hours is obtained from the AO. However, DSTs may be allowed to continue at night if the test was initiated during daylight hours and the rate of flow is stabilized and if adequate lighting is available (i.e., lighting which is adequate for visibility and vaporproof for safe operations). Packers can be released, but tripping should not begin before daylight unless prior approval is obtained from the AO.

A cement bond log (CBL) will be run at a minimum from the production casing shoe to $\pm 2865'$ and shall be utilized to determine the top of cement (TOC) and bond quality for production casing. Submit a field copy of the CBL to this office.

Whether the well is completed as a dry hole or as a producer, "Well Completion and Recompletion Report and Log" (Form 3160-4) will be submitted not later than 30 days after completion of the well or after completion of operations being performed, in accordance with 43 CFR 3164. Two copies of all logs, core descriptions, core analyses, well-test data, geologic summaries, sample description, and all other surveys or data obtained and compiled during the drilling, workover, and/or completion operations, will be filed with Form 3160-4. Samples (cuttings, fluids, and/or gases) will be submitted when requested by the AO.

6. Notifications of Operations

No location will be constructed or moved, no well will be plugged, and no drilling or workover equipment will be removed from a well to be placed in a suspended status without prior approval of the AO. If operations are to be suspended, prior approval of the AO will be obtained and notification given before resumption of operations.

The Vernal District Office shall be notified, during regular work hours (7:45 a.m.-4:30 p.m., Monday through Friday except holidays), at least 24 hours prior to spudding the well.

Operator shall report production data to MMS pursuant to 30 CFR 216.5 using form MMS/3160.

Immediate Report: Spills, blowouts, fires, leaks, accidents, or any other unusual occurrences shall be promptly reported in accordance with the requirements of NTL-3A or its revision.

If a replacement rig is contemplated for completion operations, a "Sundry Notice" (Form 3160-5) to that effect will be filed, for prior approval of the AO, and all conditions of this approved plan are applicable during all operations conducted with the replacement rig.

The date on which production is commenced or resumed will be construed for oil wells as the date on which liquid hydrocarbons are first sold or shipped from a temporary storage facility, such as a test tank, and for which a run ticket is required to be generated or, the date on which liquid hydrocarbons are first produced into a permanent storage facility, whichever first occurs; and, for gas wells as the date on which associated liquid hydrocarbons are first sold or shipped from a temporary storage facility, such as a test tank, and for which a run ticket is required to be generated or, the date on which gas is first measured through permanent metering facilities, whichever first occurs.

Should the well be successfully completed for production, the AO will be notified when the well is placed in a producing status. Such notification will be sent by telegram or other written communication, not later than five (5) days following the date on which the well is placed on production.

Gas produced from this well may not be vented or flared beyond an initial authorized test period of 30 days or 50 MMCF following its completion, whichever occurs first, without the prior written approval of the Authorized Officer. Should gas be vented or flared without approval beyond the authorized test period, the operator may be directed to shut-in the well until the gas can be captured or approval to continue venting or flaring as uneconomic is granted and the operator shall be required to compensate the lessor for that portion of the gas vented or flared without approval which is determined to have been avoidably lost.

A schematic facilities diagram as required by 43 CFR 3162.7-5 (b.9. d.), and shall be submitted to the appropriate District Office within sixty (60) days of installation or first production, whichever occurs first. All site security regulations as specified in Onshore Oil & Gas Order No. 3 shall be adhered to. All product lines entering and leaving hydrocarbon storage tanks will be effectively sealed in accordance with 43 CFR 3162.7-5 (b. 4).

No well abandonment operations will be commenced without the prior approval of the AO. In the case of newly drilled dry holes or failures, and in emergency situations, oral approval will be obtained from the AO. A "Subsequent Report of Abandonment" Form 3160-5, will be filed with the AO within thirty (30) days following completion of the well for abandonment. This report will indicate where plugs were placed and the current status of surface restoration. Final abandonment will not be approved until the surface reclamation work required by the approved APD or approved abandonment notice has been completed to the satisfaction of the AO or his representative, or the appropriate Surface Managing Agency.

7. Other Information

All loading lines will be placed inside the berm surrounding the tank battery.

All off-lease storage, off-lease measurement, or commingling on-lease or off-lease will have prior written approval from the AO.

Gas meter runs for each well will be located within 500 feet of the wellhead. The gas flowline will be buried or anchored down from the wellhead to the meter and within 500 feet downstream of the meter run or any production facilities. Meter runs will be housed and/or fenced.

The oil and gas measurement facilities will be installed on the well location. The oil and gas meters will be calibrated in place prior to any deliveries. Tests for meter accuracy will be conducted monthly for the first three months on new meter installations and at least quarterly thereafter. The AO will be provided with a date and time for the initial meter calibration and all future meter proving schedules. A copy of the meter calibration reports will be submitted to the Vernal District Office. All meter measurement facilities will conform with Onshore Oil & Gas Order No. 4 for liquid hydrocarbons and Onshore Oil & Gas Order No. 5 for natural gas measurement.

The use of materials under BLM jurisdiction will conform to 43 CFR 3610.2-3.

There will be no deviation from the proposed drilling and/or workover program without prior approval from the AO. Safe drilling and operating practices must be observed. All wells, whether drilling, producing, suspended, or abandoned will be identified in accordance with 43 CFR 3162.

"Sundry Notice and Report on Wells" (Form 3160-5) will be filed for approval for all changes of plans and other operations in accordance with 43 CFR 3162.3-2.

Section 102(b)(3) of the Federal Oil and Gas Royalty Management Act of 1982, as implemented by the applicable provisions of the operating regulations at Title 43 CFR 3162.4-1(c), requires that "not later than the 5th business day after any well begins production on which royalty is due anywhere on a lease site or allocated to a lease site, or resumes production in the case of a well which has been off production for more than 90 days, the operator shall notify the authorized officer by letter or sundry notice, Form 3160-5, or orally to be followed by a letter or sundry notice, of the date on which such production has begun or resumed."

If you fail to comply with this requirement in the manner and time allowed, you shall be liable for a civil penalty of up to \$10,000 per violation for each day such violation continues, not to exceed a maximum of 20 days. See Section 109(c)(3) of the Federal Oil and Gas Royalty Management Act of 1982 and the implementing regulations at Title 43 CFR 3162.4-1(b)(5)(ii).

APD approval is valid for a period of one (1) year from the signature date. An extension period may be granted, if requested, prior to the expiration of the original approval period.

In the event after-hours approvals are necessary, please contact one of the following individuals:

Wayne Bankert (801) 789-4170
Petroleum Engineer

Ed Forsman (801) 789-7077
Petroleum Engineer

BLM FAX Machine (801) 781-4410

EPA'S LIST OF NONEXEMPT EXPLORATION AND PRODUCTION WASTES

While the following wastes are nonexempt, they are not necessarily hazardous.

- Unused fracturing fluids or acids
- Gas plant cooling tower cleaning wastes
- Painting wastes
- Oil and gas service company wastes, such as empty drums, drum rinsate, vacuum truck rinsate, sandblast media, painting wastes, spent solvents, spilled chemicals, and waste acids
- Vacuum truck and drum rinsate from trucks and drums, transporting or containing nonexempt waste
- Refinery wastes
- Liquid and solid wastes generated by crude oil and tank bottom reclaimers
- Used equipment lubrication oils
- Waste compressor oil, filters, and blowdown
- Used hydraulic fluids
- Waste solvents
- Waste in transportation pipeline-related pits
- Caustic or acid cleaners
- Boiler cleaning wastes
- Boiler refractory bricks
- Incinerator ash
- Laboratory wastes
- Sanitary wastes
- Pesticide wastes
- Radioactive tracer wastes
- Drums, insulation and miscellaneous solids.

CONDITIONS OF APPROVAL
SURFACE USE PLAN OF OPERATIONS

Location of Existing and/or Proposed Facilities

All permanent (on site for six months or longer) structures constructed or installed (including pumping units) will be painted a flat, non-reflective, earthtone color to match one of the standard environmental colors, as determined by the Rocky Mountain Five State Interagency Committee. All facilities will be painted within 6 months of installation. Facilities required to comply with O.S.H.A. (Occupational Safety and Health Act) will be excluded.

Plans for Restoration of Surface

a. Producing Location

Immediately upon well completion, the location and surrounding area will be cleared of all unused tubing, equipment, debris, materials, trash, and junk not required for production.

Immediately upon well completion, any hydrocarbons on the pit shall be removed in accordance with 43 CFR 3162.7-1.

If a plastic nylon reinforced liner is used, it shall be torn and perforated before backfilling of the reserve pit.

The reserve pit and that portion of the location not needed for production facilities/operations will be recontoured to the approximate natural contours. The reserve pit will be reclaimed within 6 months from the date of well completion. Before any dirt work takes place, the reserve pit must be completely dry and all cans, barrels, pipe, etc., will be removed.

Contact appropriate surface management agency for required seed mixture.

b. Dry Hole/Abandoned Location

At such time as the well is plugged and abandoned, the operator shall submit a subsequent report of abandonment and BLM will attach the appropriate surface rehabilitation conditions of approval.

Other Additional Information

- a. The operator is responsible for informing all persons in the area who are associated with this project that they will be subject to prosecution for knowingly disturbing historic or archaeological sites, or for collecting artifacts. If historic or archaeological materials are uncovered during construction, the operator is to immediately stop work that might further disturb such materials, and contact the authorized officer (AO). Within five working days the AO will inform the operator as to:

- whether the materials appear eligible for the National Register of Historic Places;

- the mitigation measures the operator will likely have to undertake before the site can be used (assuming in situ preservation is not necessary); and

- a time frame for the AO to complete an expedited review under 36 CFR 800.11 to confirm, through the State Historic Preservation Officer, that the findings of the AO are correct and that mitigation is appropriate.

If the operator wishes, at any time, to relocate activities to avoid the expense of mitigation and/or the delays associated with this process, the AO will assume responsibility for whatever recordation and stabilization of the exposed materials may be required. Otherwise, the operator will be responsible for mitigation costs. The AO will provide technical and procedural guidelines for the conduct of mitigation. Upon verification from the AO that required mitigation has been completed, the operator will then be allowed to resume construction.

- b. The operator will control noxious weeds along rights-of-way for roads, pipelines, well sites, or other applicable facilities. A list of noxious weeds may be obtained from the BLM, or the appropriate County Extension Office. On BLM administered land it is required that a Pesticide Use Proposal shall be submitted, and given approval, prior to the application of herbicides or other pesticides or possible hazardous chemicals.
- c. Drilling rigs and/or equipment used during drilling operations on this wellsite will not be stacked or stored on Federal Lands after the conclusion of drilling operations or at any other time without BLM authorization. However, if BLM authorization is obtained, it is only a temporary measure to allow time to make arrangements for permanent storage on commercial facilities. (The BLM does not seek to compete with private industry. There are commercial facilities available for stacking and storing drilling rigs.)

Additional Surface Stipulations

No construction or drilling activities shall be conducted between May 15 and June 20 because of crucial pronghorn habitat. Modifications to the Surface Use Plan are to protect the pronghorn during the kidding period.

No construction or drilling activities shall be conducted from March 15 to June 15 because of the strutting and nesting sage grouse. This location is within a 2-mile radius of a sage grouse strutting ground.



A silt catchment dam and basin will be constructed according to BLM specifications approximately 700 ft. south of the location, where flagged. A copy of the BLM specifications, "Minimum Standards for Dams Impounding Under 10-acre Feet" is attached hereto.

All lease and/or unit operations will be conducted in such a manner that full compliance is made with all applicable laws, regulations, Onshore Oil and Gas Orders, the approved plan of operations, and any applicable Notice to Lessees. The operator is fully responsible for the actions of his subcontractors. A copy of these conditions will be furnished the field representative to insure compliance.

A complete copy of the approved APD and ROW grant, if applicable, shall be on location during construction of the location and drilling activities.

The operator or his/her contractor shall contact the BLM Office at (801) 789-1362 forty-eight (48) hours prior to construction activities.

The BLM Office shall be notified upon site completion prior to moving on the drilling rig.



NOTES

- Embankment slopes & dimensions shall be as shown on the Work Summary Chart
- Cut spillway to be constructed where no adequate natural spillway exists

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT DIVISION OF ENGINEERING SYSTEMS DENVER SERVICE CENTER	
TYPICAL MINOR RETENTION DAM	
DESIGNED <i>Ronald Twist</i>	
REVIEWED <i>J.D. Sedillo</i>	
APPROVED <i>Lincoln & Co.</i>	
DRAWN P.W. Twist J.D. Sedillo	SCALE NONE
DATE MARCH 9, 1984	SHEET OF
DRAWING NO. 02294-2	

DIVISION OF OIL, GAS AND MINING

SPUDDING INFORMATION

Name of Company: CHEVRON USA

Well Name: RED WASH UNIT 311

Api No. 43-047-32628

Section 26 Township 7S Range 24E County UINTAH

Drilling Contractor

Rig #

SPUDDED: Date 4/28/95

Time 9:00 AM

How DRY HOLE

Drilling will commence

Reported by KEVIN KOPP

Telephone #

Date: 5/2/95 Signed: FRM

State of Utah
Division of Oil, Gas and Mining

ENTITY ACTION FORM - FORM 6

OPERATOR: **Chevron USA Production Company**
ADDRESS: **11002 East 17500 South**
Vernal, Utah 84078-8526 (801)781-4302

OPERATOR ACCT. No. N0210

Action Code	Current Entity No.	New Entity No.	API Number	Well Name	QQ	SC	TP	RG	County	Spud Date	Effective Date
B	99999	05670	43-047-32628	Red Wash Unit #311	NE $\frac{1}{4}$ SW $\frac{1}{4}$	S26	T7S	R24E	Uintah	4/27/95	

WELL 1 COMMENTS:

Well drilled as part of the Green River Participating Area within the Red Wash Unit

Entity added 5-4-95. Lee

WELL 2 COMMENTS:

WELL 3 COMMENTS:

WELL 4 COMMENTS:


WELL 5 COMMENTS:

ACTION CODES (See instructions on back of form)

- A - Establish new entity for new well (single well only)
- B - Add new well to existing entity (group or unit well)
- C - Re-assign well from one existing entity to another existing entity
- D - Re-assign well from one existing entity to a new entity
- E - Other (explain in comments section)

NOTE: Use COMMENT section to explain why each Action Code was selected

(3/89)



Dana Rough
Signature

Operations Assistant 5/1/95
Title Date

Phone No. (801) 781-4302

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED

Budget Bureau No. 1004-0135

Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.

USE "APPLICATION FOR PERMIT -" For such proposals.

MAY 5 1995

5. Lease Designation and Serial No.

SL-071965

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

CHEVRON U.S.A. PRODUCTION CO.

3. Address and Telephone No.

P. O. BOX 4876

HOUSTON, TX 77210

ATTN: MARY COHLMIA

(713) 754-5068

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1512' FSL, 1370' FWL

NE SW Sec. 26-T7S, R24E, SLB&M

Red Wash

8. Well Name and No.

Red Wash #311

9. API Well No.

43-047-32628

10. Field and Pool, or Exploratory Area

Red Wash/Green River

11. County or Parish, State

Uintah Co., Utah

12 CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☒ Notice of Intent
- ☐ Subsequent Report
- ☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
- ☐ Recompletion
- ☐ Plugging Back
- ☐ Casing Repair
- ☐ Altering Casing
- ☐ Other

- ☐ Change of Plans
- ☐ New Construction
- ☐ Non-Routine Fracturing
- ☐ Water Shut-off
- ☐ Conversion to Injection
- ☐ Dispose Water

(Note: Report results of multiple completions on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

THE PURPOSE OF THIS SUNDRY IS TO REPORT THE SPUD OF THE ABOVE WELL ON APRIL 28, 1995.

3-BLM VERNAL, 2-UTOGC, DRLG, RANGELY

14. I hereby certify that the foregoing is true and correct.

Signed: Mary Cohlmia

Title: DRILLING TECHNICAL ASSISTANT

Date: 5/2/95

(This space for Federal or State office use)

Approved by: _____

Title: _____

Date: _____

Conditions of approval, if any:

Title 18 U. S. C. Section 1001 makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

* See Instruction on Reverse Side

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED

Budget Bureau No. 1004-0135

Expires: March 31, 1993

5. Lease Designation and Serial No.

SL-071965

Indian, Allottee or Tribe Name

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different formation.

USE "APPLICATION FOR PERMIT -" For such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

CHEVRON U.S.A. PRODUCTION CO.

3. Address and Telephone No.

P. O. BOX 4876

HOUSTON, TX 77210

ATTN: MARY COHLMIA

(713) 754-5068

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1512' FSL, 1370' FWL

NE SW Sec. 26-T7S, R24E, SLB&M

7. If Unit or CA, Agreement Designation

Red Wash

8. Well Name and No.

Red Wash #311

9. API Well No.

43-047-32628

10. Field and Pool, or Exploratory Area

Red Wash/Green River

11. County or Parish, State

Uintah Co., Utah

12 CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☒ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☐ Other

- ☒ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completions on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

THE PURPOSE OF THIS SUNDRY IS TO REPORT THE FOLLOWING CHANGES FROM THE ORIGINAL APD OF THE ABOVE WELL.

1. 6-1/2" hole size.
2. Well was plugged and abandoned on 6/1/95
3. Cement Plugs - 70 sxs 4793'-5126',
70 sxs 3167'-3475'
50 sxs 2217'-2451'
45 sxs 245'-445'
25 sxs surface to 65' KB

3-BLM VERNAL, 2-UTOGC, DRLG, RANGELY

14. I hereby certify that the foregoing is true and correct.

Signed: Mary Cohlmia

Title: DRILLING TECHNICAL ASSISTANT

Date: 6/6/95

(This space for Federal or State office use)

Approved by: _____

Title: _____

Date: _____

Conditions of approval, if any:

Title 18 U. S. C. Section 1001 makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

* See Instruction on Reverse Side

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS, GAS & MINING
Do not use this form for proposals to drill or to deepen or reentry to a **UNIT OF OIL, GAS & MINING**
Use "APPLICATION FOR PERMIT--" for such proposals

Lease Designation and Serial No.
SL-071965

6. If Indian, Allottee or Tribe Name

N/A

7. If Unit or CA, Agreement Designation

RED WASH UNIT

8. Well Name and No.

RED WASH UNIT 311

9. API Well No.

43-047-32628

10. Field and Pool, or Exploratory Area

RED WASH - GREEN RIVER

11. County or Parish, State

UINTAH, UTAH

SUBMIT IN TRIPLICATE

1. Type of Well

Oil

Gas

☐

Well

☒

Well

☐

Other

2. Name of Operator

CHEVRON U.S.A. PRODUCTION COMPANY

3. Address and Telephone No.

11002 E. 17500 S. VERNAL, UT 84078-8526

Steve McPherson in Red Wash (801) 781-4310

or Gary Scott in Rangely, CO. (970) 675-3791

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1512' FSL & 1370' FWL (NE SW) SECTION 26, T7S, R24E, SLBM

12. **CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA**

TYPE OF SUBMISSION

☐

Notice of Intent

☐

Subsequent Report

☒

Final Abandonment Notice

TYPE OF ACTION

☒

Abandonment

☐

Recompletion

☐

Plugging Back

☐

Casing Repair

☐

Altering Casing

☐

Other

☐

Change of Plans

☐

New Construction

☐

Non-Routine Fracturing

☐

Water Shut-Off

☐

Conversion to Injection

☐

Dispose Water

(Note) Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work)

THE ABOVE WELL HAS BEEN RESEEDED AND RECLAIMED PER SPECIFICATIONS.

14. I hereby certify that the foregoing is true and correct.

Signed **G.D. SCOTT**

Title **DRILLING TECHNICIAN**

Date **December 19, 1995**

(This space for Federal or State office use)

Approved by:

Title

Date

Conditions of approval, if any

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN DUPLICATE
(See instructions on
reverse side).

Form approved.
Budget Bureau No. 1004-0137
Expires August 31, 1985

WELL COMPLETION OR RECOMPLETION REPORT AND LOG *

1a. TYPE OF WELL OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> DRY <input checked="" type="checkbox"/> Other _____		7. UNIT AGREEMENT NAME RED WASH UNIT																															
b. TYPE OF COMPLETION NEW WELL <input checked="" type="checkbox"/> WORK OVER <input type="checkbox"/> DEEP-EN <input type="checkbox"/> PLUG BACK <input type="checkbox"/> DIFF. RESVR <input type="checkbox"/> Other _____		8. FARM OR LEASE NAME RED WASH																															
2. NAME OF OPERATOR CHEVRON U.S.A. PRODUCTION COMPANY		9. WELL NO. 311																															
3. ADDRESS OF OPERATOR 11002 E. 17500 S. VERNAL, UT 84078-8526		10. FIELD AND POOL, OR WILDCAT RED WASH GREEN RIVER																															
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements)* At surface 1512' FSL & 1370' FWL (NE SW) At top rod. interval reported below At total depth		11. SEC., T., R., M., OR BLOCK AND SURVEY OR AREA SEC. 26, T7S, R24E, SLBM																															
14. PERMIT NO. 43-047-32628		DATE ISSUED 1/24/95																															
12. COUNTY OR PARISH UINTAH		13. STATE UTAH																															
15. DATE SPUDDED 4/28/95	16. DATE T.D. REACHED 5/29/95	17. DATE COMPL. (Ready to prod.) 6/2/95 P&A'd	18. ELEVATIONS (DF, RKB, RT, GR, ETC.)* 5673 DF, 5674 KB, 5662 GR																														
19. ELEV. CASINGHEAD	20. TOTAL DEPTH, MD & TVD 5225																																
21. PLUG BACK T.D., MD & TVD			22. IF MULTIPLE COMPL., HOW MANY*																														
23. INTERVALS DRILLED BY ALL			24. PRODUCING INTERVAL(S), OF THIS COMPLETION--TOP, BOTTOM, NAME (MD AND TVD)* NONE PLUGGED AND ABANDONED																														
25. WAS DIRECTIONAL SURVEY MADE NO			26. TYPE ELECTRIC AND OTHER LOGS RUN DIFL/GR/SP, CDL/CN/GR FMT 6-6-96																														
27. WAS WELL CORED NO			28. CASING RECORD (Report all strings set in well)																														
<table border="1" style="width:100%"><tr><th>CASING SIZE</th><th>WEIGHT, LB./FT.</th><th>DEPTH SET (MD)</th><th>HOLE SIZE</th><th>CEMENTING RECORD</th><th>AMOUNT PULLED</th></tr><tr><td>8 5/8"</td><td>24#</td><td>360</td><td>12 1/4"</td><td>220 SACKS CLASS G CEMENT</td><td></td></tr><tr><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td></tr><tr><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td></tr><tr><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td></tr></table>				CASING SIZE	WEIGHT, LB./FT.	DEPTH SET (MD)	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED	8 5/8"	24#	360	12 1/4"	220 SACKS CLASS G CEMENT																			
CASING SIZE	WEIGHT, LB./FT.	DEPTH SET (MD)	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED																												
8 5/8"	24#	360	12 1/4"	220 SACKS CLASS G CEMENT																													
29. LINER RECORD																																	
<table border="1" style="width:100%"><tr><th>SIZE</th><th>TOP (MD)</th><th>BOTTOM (MD)</th><th>SACKS CEMENT*</th><th>SCREEN (MD)</th></tr><tr><td> </td><td> </td><td> </td><td> </td><td> </td></tr><tr><td> </td><td> </td><td> </td><td> </td><td> </td></tr><tr><td> </td><td> </td><td> </td><td> </td><td> </td></tr></table>				SIZE	TOP (MD)	BOTTOM (MD)	SACKS CEMENT*	SCREEN (MD)																									
SIZE	TOP (MD)	BOTTOM (MD)	SACKS CEMENT*	SCREEN (MD)																													
30. TUBING RECORD																																	
<table border="1" style="width:100%"><tr><th>SIZE</th><th>DEPTH SET (MD)</th><th>PACKER SET (MD)</th></tr><tr><td> </td><td> </td><td> </td></tr><tr><td> </td><td> </td><td> </td></tr><tr><td> </td><td> </td><td> </td></tr></table>				SIZE	DEPTH SET (MD)	PACKER SET (MD)																											
SIZE	DEPTH SET (MD)	PACKER SET (MD)																															
31. PERFORATION RECORD (Interval, size and number) BALANCED PLUG 5096-4896' 70 SACKS BALANCED PLUG 3636-3336' 90 SACKS BALANCED PLUG 2554-2354' 65 SACKS BALANCED PLUG 477-277' 70 SACKS BALANCED PLUG 50' TO SURFACE 30 SACKS																																	
32. ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC. <div style="border: 2px solid black; padding: 5px; text-align: center;">RECEIVED MAY 10 1996 DIV. OF OIL, GAS & MINING</div>																																	
33. DATE FIRST PRODUCTION NONE																																	
PRODUCTION METHOD (Flowing, gas lift, pumping--size and type of pump) PLUGGED AND ABANDONED																																	
WELL STATUS (Producing or shut-in) PLUGGED AND ABANDONED																																	
DATE OF TEST NONE																																	
HOURS TESTED																																	
CHOKE SIZE																																	
PROD'N FOR TEST PERIOD																																	
FLOW. TUBING PRESS.																																	
CASING PRESSURE																																	
CALCULATED 24-HOUR RATE																																	
OIL--BBL.																																	
GAS--MCF																																	
WATER--BBL.																																	
OIL GRAVITY--API (CORR.)																																	
34. DISPOSITION OF GAS (Sold, used for fuel, vented, etc.)																																	
TEST WITNESSED BY																																	
35. LIST OF ATTACHMENTS NONE - LOGS PREVIOUSLY SENT																																	
36. I hereby certify that the foregoing and attached information is complete and correct as determined from all available records																																	
SIGNED <u>G.D. SCOTT</u> <i>G.D. Scott</i> TITLE <u>DRILLING TECHNICIAN</u> DATE <u>May 6, 1996</u>																																	

(See Instructions and Spaces for Additional Data on Reverse Side)

37. SUMMARY OF POROUS ZONES: (Show all important zones of porosity and contents thereof, cored intervals; and all drill-stem tests, including depth interval tested, cushion used, time tool open, flowing and shut-in pressures, and recoveries):				38. GEOLOGIC MARKERS		
FORMATION	TOP	BOTTOM	DESCRIPTION, CONTENTS, ETC.	NAME	MEAS. DEPTH	TOP TRUE VERT. DEPTH
UINTAH GREEN RIVER	SURFACE 2335	2335 5105		TOP OF OIL SHALE BASE OF OIL SHALE GREEN RIVER - F GREEN RIVER - G GREEN RIVER - K GREEN RIVER - Kb GREEN RIVER - L	3203 3344 3818 4042 4705 4828 4934	
WASATCHII	5105					

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir
Use "APPLICATION FOR PERMIT--" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

Oil

Gas

☐

Well

☐

Well

☒

Other

MULTIPLE WELLS SEE ATTACHED LIST

2. Name of Operator

CHEVRON U.S.A. INC.

3. Address and Telephone No

11002 E. 17500 S. VERNAL, UT 84078-8526

(801) 781-4300

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

5. Lease Designation and Serial No.

N/A

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

RED WASH UNIT

I-SEC NO 761

8. Well Name and No.

9. API Well No.

10. Field and Pool, or Exploratory Area

RED WASH - GREEN RIVER

11. County or Parish, State

UINTAH, UTAH

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☐

Notice of Intent

☒

Subsequent Report

☐

Final Abandonment Notice

TYPE OF ACTION

☐

Abandonment

☐

Recompletion

☐

Plugging Back

☐

Casing Repair

☐

Altering Casing

☒

Other CHANGE OF OPERATOR

☐

Change of Plans

☐

New Construction

☐

Non-Routine Fracturing

☐

Water Shut-Off

☐

Conversion to Injection

☐

Dispose Water

(Note) Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work)

As of January 1, 2000 Chevron U.S.A. INC. resigns as Operator of the Red Wash Unit.
The Unit Number is I-SEC NO 761 effective October 31, 1950.

The successor operator under the Unit Agreement will be
Shenandoah Energy Inc.
475 17th Street, Suite 1000
Denver, CO 80202

Agreed and accepted to this 29th day of December, 1999

Shenandoah Energy Inc.

By: Mitchell L. Solich
President

RECEIVED

DEC 30 1999

DIVISION OF OIL, GAS & MINING

14. I hereby certify that the foregoing is true and correct.

Signed A. E. Wacker

Title Assistant Secretary

Date 12/29/99

(This space for Federal or State office use)

Approved by:

Title

Date

Conditions of approval, if any

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.



United States Department of the Interior

BUREAU OF LAND MANAGEMENT

Utah State Office
P.O. Box 45155
Salt Lake City, UT 84145-0155

RECEIVED

FEB 07 2000

DIVISION OF
OIL, GAS AND MINING

IN REPLY REFER TO
UT-931

February 4, 2000

Shenandoah Energy Inc.
Attn: Rae Cusimano
475 17th Street, Suite 1000
Denver, Colorado 80202

Re: Red Wash Unit
Uintah County, Utah

Gentlemen:

On December 30, 1999, we received an indenture whereby Chevron U.S.A. Inc. resigned as Unit Operator and Shenandoah Energy Inc. was designated as Successor Unit Operator for the Red Wash Unit, Uintah County, Utah.

This indenture was executed by all required parties and the signatory parties have complied with Sections 5 and 6 of the unit agreement. The instrument is hereby approved effective February 4, 2000. In approving this designation, the Authorized Officer neither warrants nor certifies that the designated party has obtained all required approval that would entitle it to conduct operations under the Red Wash Unit Agreement.

Your statewide (Utah) oil and gas bond No. 0969 will be used to cover all operations within the Red Wash Unit.

It is requested that you notify all interested parties of the change in unit operator. Copies of the approved instruments are being distributed to the appropriate federal offices, with one copy returned herewith.

Sincerely,

/s/ Robert A. Henricks

Robert A. Henricks
Chief, Branch of Fluid Minerals

Enclosure

cc: Chevron U.S.A. Inc.

bcc: Field Manager - Vernal (w/enclosure)
~~Division of Oil, Gas & Mining~~
Minerals Adjudication Group U-932
File - Red Wash Unit (w/enclosure)
MMS - Data Management Division
Agr. Sec. Chron
Fluid Chron

UT931:TAThompson:tt:2/4/00

Well Status Report
Utah State Office
Bureau of Land Management

Lease	Api Number	Well Name	QTR	Section	Township	Range	Well Status	Operator
UTU0559	4304731581	293 (22-22A) RED WAS SENW	22	T	7S	R22E	OSI	CHEVRON U S A INCORPORATED
UTU02148	4304731582	294 (24-18C) RED WAS SESW	18	T	7S	R24E	PGW	CHEVRON U S A INCORPORATED
UTU081	4304731577	295 (11-22B) RED WAS NWNW	22	T	7S	R23E	TA	CHEVRON U S A INCORPORATED
UTU0566	4304731578	296 (12-35B) RED WAS SWNW	35	T	7S	R23E	POW	CHEVRON U S A INCORPORATED
UTU081	4304731579	297 (24-15B) RED WAS SESW	15	T	7S	R23E	POW	CHEVRON U S A INCORPORATED
UTU0566	4304731679	298 (22-27B) RED WAS SENW	27	T	7S	R23E	TA	CHEVRON U S A INCORPORATED
UTU0116	4304733018	299 SWNE	18	T	7S	R23E	POW	CHEVRON U S A INCORPORATED
UTU082	4304715136	3 (34-23B) RED WASH SWSE	23	T	7S	R23E	POW	CHEVRON U S A INCORPORATED
UTU081	4304715157	30 (23-13B) RED WASH NESW	13	T	7S	R23E	POW	CHEVRON U S A INCORPORATED
UTU081	4304731682	301 (43-15B) RED WAS NESE	15	T	7S	R23E	TA	CHEVRON U S A INCORPORATED
UTU082	4304731683	302 (22-24B) RED WAS SENW	24	T	7S	R23E	TA	CHEVRON U S A INCORPORATED
UTU0116	4304731819	303 (34-17B) RED WAS SWSE	17	T	7S	R23E	POW	CHEVRON U S A INCORPORATED
UTU0830	4304732538	305 NENE	4	T	8S	R24E	PGW	CHEVRON U S A INCORPORATED
UTU093	4304732629	306 NESW	23	T	7S	R24E	POW	CHEVRON U S A INCORPORATED
STATE	4304732632	307 SWSW	16	T	7S	R24E	ABD	CHEVRON U S A INCORPORATED
UTSL071965	4304732627	308 SESW	28	T	7S	R24E	P+A	CHEVRON U S A INCORPORATED
UTU081	4304715158	31 (34-22B) RED WASH SWSE	22	T	7S	R23E	POW	CHEVRON U S A INCORPORATED
UTSL071965	4304732628	311 NESW	26	T	7S	R24E	P+A	CHEVRON U S A INCORPORATED
UTSL071963	4304732595	312 SWNE	34	T	7S	R24E	ABD	CHEVRON U S A INCORPORATED
UTU02149	4304732630	313 NESW	20	T	7S	R24E	ABD	CHEVRON U S A INCORPORATED
UTSL071965	4304732626	314 SESW	29	T	7S	R24E	ABD	CHEVRON U S A INCORPORATED
UTU081	4304715160	33 (14-14B) RED WASH SWSW	14	T	7S	R23E	TA	CHEVRON U S A INCORPORATED
UTU081	4304715161	34 (23-14B) RED WASH NESW	14	T	7S	R23E	WIW	CHEVRON U S A INCORPORATED
UTU081	4304715162	35 (43-13B) RED WASH NESE	13	T	7S	R23E	TA	CHEVRON U S A INCORPORATED
UTU081	4304715163	36 (32-13B) RED WASH SWNE	13	T	7S	R23E	POW	CHEVRON U S A INCORPORATED
UTU0823	4304715164	37 (41-25B) RED WASH NENE	25	T	7S	R23E	ABD	CHEVRON U S A INCORPORATED
UTU082	4304715165	38 (14-23B) RED WASH SWSW	23	T	7S	R23E	POW	CHEVRON U S A INCORPORATED
UTU0561	4304715166	39 (14-24A) RED WASH SWSW	24	T	7S	R22E	TA	CHEVRON U S A INCORPORATED
UTU081	4304715137	4 (41-22B) RED WASH NENE	22	T	7S	R23E	TA	CHEVRON U S A INCORPORATED
UTU082	4304715167	40 (21-24B) RED WASH NENW	24	T	7S	R23E	POW	CHEVRON U S A INCORPORATED
UTU081	4304715168	41 (34-13B) RED WASH SWSE	13	T	7S	R23E	POW	CHEVRON U S A INCORPORATED
UTSL071965	4304715169	42 (21-29C) RED WASH NENW	29	T	7S	R24E	PGW	CHEVRON U S A INCORPORATED
UTU0116	4304715170	43 (12-17B) RED WASH SWNW	17	T	7S	R23E	POW	CHEVRON U S A INCORPORATED
UTU0829	4304715171	44 (32-33C) RED WASH SWNE	33	T	7S	R24E	PGW	CHEVRON U S A INCORPORATED
UTU02030	4304715172	45 (23-30B) RED WASH NESW	30	T	7S	R23E	TA	CHEVRON U S A INCORPORATED
UTU080	4304715173	46 (41-21C) RED WASH NENE	21	T	7S	R24E	PGW	CHEVRON U S A INCORPORATED
UTU02030	4304715174	48 (32-19B) RED WASH SWNE	19	T	7S	R23E	TA	CHEVRON U S A INCORPORATED
UTU02025	4304715175	49 (12-29B) RED WASH SWNW	29	T	7S	R23E	TA	CHEVRON U S A INCORPORATED
UTU082	4304715138	5 (41-23B) RED WASH NENE	23	T	7S	R23E	POW	CHEVRON U S A INCORPORATED
UTU0559	4304715176	50 (14-23A) RED WASH SWSW	23	T	7S	R22E	POW	CHEVRON U S A INCORPORATED
STATE	4304715177	51 (12-16B) RED WASH SWNW	16	T	7S	R23E	POW	CHEVRON U S A INCORPORATED
UTU0116	4304715178	52 (14-18B) RED WASH SWSW	18	T	7S	R23E	TA	CHEVRON U S A INCORPORATED
UTU0561	4304715179	53 (41-25A) RED WASH NENE	25	T	7S	R22E	POW	CHEVRON U S A INCORPORATED
UTU0559	4304715181	55 (41-21A) RED WASH NENE	21	T	7S	R22E	P+A	CHEVRON U S A INCORPORATED
UTU02030	4304715182	56 (41-28B) RED WASH NENE	28	T	7S	R23E	WIW	CHEVRON U S A INCORPORATED
UTU02148	4304715183	57 (12-18C) RED WASH SWNW	18	T	7S	R24E	POW	CHEVRON U S A INCORPORATED
UTU082	4304716477	59 (12-24B) RED WASH SWNW	24	T	7S	R23E	WIW	CHEVRON U S A INCORPORATED
UTU0567	4304716482	6 (41-21B) RED WASH NENE	21	T	7S	R23E	WIW	CHEVRON U S A INCORPORATED
UTU02025	4304715184	60 (43-30B) RED WASH NESE	30	T	7S	R23E	TA	CHEVRON U S A INCORPORATED

OPERATOR CHANGE WORKSHEET

ROUTING

1. GLH		4-KAS
2. CDW	✓	5-SPD ✓
3. JLT		6-FILE

Enter date after each listed item is completed

X Change of Operator (Well Sold)

Designation of Agent

Operator Name Change (Only)

Merger

The operator of the well(s) listed below has changed, effective:

01-01-2000**FROM:** (Old Operator):

CHEVRON USA INC

Address: 11002 E. 17500 S.

VERNAL, UT 84078-8526

Phone: 1-(435)-781-4300

Account No. N0210

TO: (New Operator):

SHENANDOAH ENERGY INC

Address: 11002 E. 17500 S.

VERNAL, UT 84078

Phone: 1-(435)-781-4300

Account N4235

CA No.

Unit: RED WASH

WELL(S)

NAME	API NO.	ENTITY NO.	SEC. TWN RNG	LEASE TYPE	WELL TYPE	WELL STATUS
RWU 39 (14-24A)	43-047-15166	5670	24-07S-22E	FEDERAL	OW	TA
RWU 35 (43-13B)	43-047-15162	5670	13-07S-23E	FEDERAL	OW	TA
RWU 36 (32-13B)	43-047-15163	5670	13-07S-23E	FEDERAL	GW	P
RWU 41 (34-13B)	43-047-15168	5670	13-07S-23E	FEDERAL	OW	P
RWU 33 (14-14B)	43-047-15160	5670	14-07S-23E	FEDERAL	GW	S
RWU 51 (12-16B)	43-047-15177	5670	16-07S-23E	STATE	OW	P
RWU 43 (12-17B)	43-047-15170	5670	17-07S-23E	FEDERAL	OW	P
RWU 52 (14-18B)	43-047-15178	5670	18-07S-23E	FEDERAL	OW	TA
RWU 4 (41-22B)	43-047-15137	5670	22-07S-23E	FEDERAL	OW	TA
RWU 38 (14-23B)	43-047-15165	5670	23-07S-23E	FEDERAL	OW	P
RWU 5 (41-23B)	43-047-15138	5670	23-07S-23E	FEDERAL	OW	P
RWU 50 (14-23A)	43-047-15176	5670	23-07S-22E	FEDERAL	OW	P
RWU 40 (21-24B)	43-047-15167	5670	24-07S-23E	FEDERAL	OW	TA
RWU 37 (41-25B)	43-047-15164	5670	25-07S-23E	FEDERAL	GW	PA
RWU 49 (12-29B)	43-047-15175	5670	29-07S-23E	FEDERAL	OW	TA
RWU 313	43-047-32630	5670	20-07S-24E	FEDERAL	GW	PA
RWU 46 (41-21C)	43-047-15173	5670	21-07S-24E	FEDERAL	GW	P
RWU 311	43-047-32628	5670	26-07S-24E	FEDERAL	OW	PA
RWU 314	43-047-32626	5670	29-07S-24E	FEDERAL	GW	PA
RWU 42 (21-29C)	43-047-15169	5670	29-07S-24E	FEDERAL	GW	P
RWU 44 (32-33C)	43-047-15171	5670	33-07S-24E	FEDERAL	GW	P
RWU 312	43-047-32595	5670	34-07S-24E	FEDERAL	GW	PA

OPERATOR CHANGES DOCUMENTATION1. (R649-8-10) Sundry or legal documentation was received from the **FORMER** operator on:12-30-19992. (R649-8-10) Sundry or legal documentation was received from the **NEW** operator on:08-09-2000

3. The new company has been checked through the **Department of Commerce, Division of Corporations Database** on: 08-23-2000
4. Is the new operator registered in the State of Utah: YES Business Number: 224885
5. If **NO**, the operator was contacted on: _____
6. **Federal and Indian Lease Wells:** The BLM and or the BIA has approved the (merger, name change, or operator change for all wells listed on Federal or Indian leases on: 02/04/2000
7. **Federal and Indian Units:** The BLM or BIA has approved the successor of unit operator for wells listed on: 02/04/2000
8. **Federal and Indian Communization Agreements ("CA"):** The BLM or the BIA has approved the operator change for all wells listed involved in a CA on: N/A
9. **Underground Injection Control ("UIC") Pro:** The Division has approved UIC Form 5, **Transfer of Authority to Inject**, for the enhanced/secondary recovery unit/project for the water disposal well(s) listed on: N/A

DATA ENTRY:

1. Changes entered in the **Oil and Gas Database** on: 09/25/2000
2. Changes have been entered on the **Monthly Operator Change Spread Sheet** on: 09/25/2000
3. Bond information entered in RBDMS on: N/A
4. Fee wells attached to bond in RBDMS on: N/A

STATE BOND VERIFICATION:

1. State well(s) covered by Bond No.: 159261960

FEE WELLS - BOND VERIFICATION/LEASE INTEREST OWNER NOTIFICATION:

1. (R649-3-1) The **NEW** operator of any fee well(s) listed has furnished a bond: N/A
2. The **FORMER** operator has requested a release of liability from their bond on: N/A
The Division sent response by letter on: N/A
3. (R649-2-10) The **FORMER** operator of the Fee wells has been contacted and informed by a letter from the Division of their responsibility to notify all interest owners of this change on: _____

FILMING:

1. All attachments to this form have been **MICROFILMED** on: 03-09-01

FILING:

1. **ORIGINALS/COPIES** of all attachments pertaining to each individual well have been filled in each well file on: _____

COMMENTS:
